



#### NOTES:

CONCRETE SIDEWALK – 5" CONCRETE WITH 4" CLASS 5

BITUMINOUS TRAIL – 2 ½" BITUMINOUS WEAR (TYPE SP 9.5 WEARING COURSE MIX SPWEA240B) WITH 6" CLASS 5

SIDEWALKS OR TRAIL CROSSING COMMERCIAL OR INDUSTRIAL DRIVEWAYS SHALL BE CONSTRUCTED TO DRIVEWAY REQUIREMENTS INDICATED ON STR-9

RESIDENTIAL STREETS SHALL BE 7 TON DESIGN UNLESS OTHERWISE SPECIFIED

SUBGRADE MUST BE APPROVED BY THE ENGINEER

① SUBCUT WHERE UNSUITABLE MATERIALS EXIST AS DIRECTED BY THE ENGINEER IN THE FIELD. SUBCUT AREAS SHALL BE BACKFILLED WITH SUITABLE MATERIAL AS DETERMINED BY THE ENGINEER



LAST REVISION  
NOVEMBER 2014

## RESIDENTIAL STREET TYPICAL SECTION

CITY OF MAPLE GROVE ENGINEERING  
& PUBLIC WORKS DEPARTMENTS

STANDARD  
PLATE #  
STR-6